



## FEATURES - POWER METER

- Measure dBm Power & dB loss
- 6 Calibrated Wavelengths; Built-In VFL
- Set Pass/Fail Thresholds
- Large, easy-to-read results
- 3.2" Color Display w/ Touchscreen
- Auto - Wave Switching
- Dynamic Range: -70dBm to + 5dBm
- 40+ Hour Battery Life & Rugged Design
- Includes 2.5mm & 1.25mm Adapters

## FEATURES - LIGHT SOURCE

- 3.2" Color Display w/ Touchscreen
- Adapter Ports: SC/APC (SM); SC/UPC (MM)
- Built-in VFL (650nm-Red)
- Auto Wave ID For Power Meter
- Output Power: -1 dBm (0 dBm Typical)
- 40+ Hour Battery Life & Rugged Design
- Available In Dual Multimode, Dual Singlemode, Quad (SM/MM)

## SPECIFICATIONS (EACH UNIT)

<b>Dimensions</b>	5.25"L x 6.125"W x 2.5"H / (133mm L x 156mm W x 64mm H)
<b>Weight</b>	1.5lbs (0.7kg)
<b>Battery</b>	Li-pol, 40+ Hr.
<b>Power Requirement</b>	USB 5V, 2A
<b>Operating Temperature</b>	-10C to 40C
<b>Storage Temperature</b>	-20C to 60C
<b>Accessories Included</b>	Soft Carry case (10"x 8.5"x 4") with inside pouch and shoulder strap, USB-A to USB-C cable (3ft.), 2 Stylus

### Optical Power Meter

<b>Wavelengths</b>	850, 1300, 1310, 1490, 1550, 1625
<b>Detector</b>	InGaAs
<b>Dynamic Range</b>	-70dBm to + 5dBm (CATV -45dBm to +23dBm)
<b>Accuracy</b>	±0.2dB

### Optical Light Source

<b>VCSEL/Laser</b>	850 & 1300/1310 & 1550
<b>Output Power</b>	-1 dBm (0dBm Typical)
<b>Modulation</b>	CW, 270 Hz, 1 kHz, 2 kHz

## ORDERING INFORMATION

<b>EZPM</b>	FIS Standard Power Meter w/dynamic range -70 to +5dBm for 850/1300/1310/1490/1550/1625nm
<b>EZPMCATV</b>	FIS CATV Power Meter w/ dynamic range -45 to +23dBm (for same 6 wavelengths)
<b>EZLS1315</b>	FIS Single Mode Dual Light Source (1310/1550nm)
<b>EZLS8513</b>	FIS Multimode Dual Light Source (850/1300nm)
<b>EZLSQUAD</b>	FIS MM/SM Quad Light Source (850/1300/1310/1550nm)