



**Part #: F1-5069APC**

F1-5069APC	Simplex APC	3.0mm	126µm
F1-506916APC	Simplex APC	1.6mm	126µm
F1-5069900APC	Simplex APC	900µm	126µm

## FEATURES

- 900µm, 1.6mm, 2.0mm, 3.0mm Cables Supported
- Fully-Compliant with EIA/TIA 604 Telcordia GR-326 Standards
- Unique Connector Design for Easy Termination

## APPLICATIONS

- Local Area Networks
- Fast Ethernet
- ATM Networks
- Fiber Channel
- Optical Transport
- Optical Access Networks

## SPECIFICATIONS

	Multimode	Singlemode
<b>Operating Temperature</b>	-40° C to +85° C	-40° C to +85° C
<b>Back Relection</b>	-25 dB Typical	- 30 dB PC Polish - 40 dB Super PC Polish - 50 dB Ultra PC Polish
<b>Repeatability</b>	< 0.2 dB	< 0.1 dB
<b>Insertion Loss</b>	< 0.4 dB	< 0.3 dB
<b>Cable Retention</b>	> 15 lbs	> 15 lbs

## MATERIAL

<b>Ferrule</b>	Ceramic
<b>Body</b>	ABS Plastic
	Stainless Steel
<b>Boot</b>	Thermoplastic Rubber