FIS FUSION SPLICE SLEEVES TAPERED ENDS - 60mm

Part #: F1-1002T50

FEATURES

- Polished stainless steel rod
- Polyolefin® clear inner tube provides moisture and cushion protection
- Teflon-coated inner tube
- Fits most popular splice trays including the FIS F1-6808 and F1-8729 (AMP 501518-1)
- Competitively priced and stocked for immediate delivery
- Installed using a heat gun or protection sleeve oven

The most popular method of protecting a fusion splice is the utilization of two heat sensitive tubes supported by a stainless steel rod. The FIS protection sleeve contains a custom inner tube made of polyolefin, which melts around the fiber to provide both moisture and cushion protection. The Teflon-treated inner tube allows easy fiber entry. The sleeve shrinks to a size that allows insertion into most fusion splice trays. This is a proven shrink tube design used in thousands of telco and communication applications.

SPECIFICATIONS

Part	**Outer Tube**			**Inner Tube**			**Stainless Steel Pin**		**Diameter After Shrink**	**Ends Type**
	ID	Thickness	Length	ID	Thickness	Length	Diameter	Length		
F11002T50	3.2±0.1	0.28±0.05	60±0.5	1.5±0.1	0.4±0.05	60±0.5	1.3±0.03	59±0.5	2.9±0.1	Tapered Ends