



## FEATURES

- Complies with IEEE802.3 and IEEE802.3u 10/100Base-TX & 100Base-FX
- 10/100Mbps and full/half duplex automatically configure in TP port
- MDI/MDI-X Auto Negotiation
- LED Indicators: Power, FX Link/Act, 100, TP Link/Act, FDX/Col.
- FCC Class A & CE approved

## SPECIFICATIONS

<b>Wavelength</b>	Multimode: 1310nm & Singlemode 1310nm
<b>Fiber Cable</b>	9/125µm Singlemode 50 or 62.5/125µm Multimode
<b>Max Distance</b>	Multimode 2km(default) Singlemode 20km(default) 40km/60km (Optional)
<b>Input Power</b>	100 to 240 VAC 50 to 60Hz
<b>Power Supply</b>	2A@+5V
<b>Size</b>	70.5mm (L) x 94mm (W) x 26.5mm(H)
<b>Environment</b>	Relative humidity: 5% to 90% Operating temperature: 0 to 60°C Storage temperature:-20 to 70°C

## ORDERING INFORMATION

<b>F1-0EC32M1-2</b>	10/100 Base-T/TX to 100 Base-FX MM/SC Converter
<b>F1-0EC32M2-2</b>	10/100 Base-T/TX to 100 Base-FX MM/ST Converter
<b>F1-0EC32S1-202</b>	10/100 Base-T/TX to 100 Base-FX SM/SC Converter