



FEATURES

- Stabilized Visible Laser
- Battery Operated - 9 Volt
- $\leq 5\text{mW}$
- Continuous Wave or Pulsed Wave
- Ruggedized Rubber Holster
- Singlemode or Multimode Use
- 10 km Range on Singlemode

CONNECTOR STYLES

- 2.5mm Universal Adapter - (Singlemode & Multimode)(SC, FC, ST)
- LC - (Singlemode & Multimode)
- FC/APC - Singlemode
- SC/APC - Singlemode

SPECIFICATIONS

Output Power	$\leq 5\text{mW}$ (4.5mW typ.)
Wavelength	650nm Typ
Battery	9 Volt Alkaline
Battery Life (typical)	20hrs continuous 30hrs modulated
Range	8km $\geq 10\text{km}$ Singlemode

Pulse Rate	1Hz
Operating Temperature	-10° to + 50° Celsius
Weight	7.5 oz
Size	6.25"L x 3.25"W x 1.25"D
Emission Indicator	Power indicator in sync when laser in use

ORDERING INFORMATION

OF-1000-UF	Visual Fault Locator with 2.5mm Universal Adapter (MM & SM)
OF-1000U-LC	Visual Fault Locator with LC Adapter (MM & SM)
OF-1000U-FCA	Visual Fault Locator with FC/APC Adapter (SM)
OF-1000U-SCA	Visual Fault Locator with SC/APC Adapter (SM)